

ROUND BALER BELTS

THE WORLD STANDARD IN QUALITY AND RELIABILITY

Dunlop Roundbaler belts. A cost-effective solution for handling the toughest of crop conditions

- Belts available for straw, hay, silage, grass and materials with a high moisture content
- Excellent durability
- Good tensile strength and transverse rigidity
- Impervious to moisture
- High impact and tear resistance
- 2-year guarantee against faulty materials and workmanship

DUNLOP CONVEYOR BELTING – VALUE FOR MONEY GUARANTEED

Dunlop Round Baler Belts come in 2 tensile strengths: 520 and 430. Regardless of the tensile strength, the construction consists of 3 extremely strong fabric plies with an extra tough, highly resilient rubber layers between the plies. This provides outstanding performance, even at high production speeds. The fabrics are impervious to moisture and have particularly low elongation characteristics, providing a multi-functional solution for a wide variety of Round Baler machines.

Both available profile surface options provide excellent grip and performance for any kind of crop.

UNRIVALLED TECHNICAL SUPPORT AND GUIDANCE

When you buy Dunlop you get more than just top quality conveyor belts because we have one of the largest, most experienced and highly trained teams of conveyor belt specialists and application engineers in the industry.

Dunlop provides an unrivalled level of customer service – visiting our customers on-site, providing advice, guidance and practical support including:

- Site visits and surveys
- Belt calculation services
- Technical training (on-site and Dunlop based)
- Splice training
- Trouble shooting and problem solving
- In-house research, testing and development
- After-sales support

24/7 HELPLINE +31 (0) 512 585 555

Our 24-hour Helpline means that we are never more than a phone call away when our customers need our help or advice. This service is extremely well supported by our extensive network of highly reputable Dunlop Authorised Distributors, Vulcanisers and Approved Agents.



TECHNICAL INFORMATION

Product Range

Type	Print	Max width mm	Standard length	Belt Thickness
HB 430/3 WPWP	Fabric/Fabric	2000	200m	7.3mm
HB 430/3 RUITWP	Diamond/Fabric	1200	200m	7.3mm
HB 520/3 WPWP	Fabric/Fabric	2000	200m	5.3mm
HB 520/3 WP-glad	Fabric/Smooth	2000	200m	5.3mm

The 520/3 types have 2 PP plies and 1 EP ply in the center to provide greater strength and is available with fabric impression on either 1 or 2 sides.

The 430 types have 2 Nylon/polyester plies which improve transverse rigidity and one double weft polyester/nylon ply in the middle for improved fastener strength.



Fabric impression

AVAILABLE WIDTHS

Dunlop Round Baler belts can be cut to any width to suit all types of machine.



Fabric, Diamond and smooth surface with fasteners

WE ARE HERE TO HELP

For more information on this product please contact our Application Engineering team on +31 (0) 512 585 555

All data and recommendations in this leaflet have been supplied to the best of our knowledge, as accurately as possible and updated to reflect the most recent technological developments. Some products may have been changed or rendered obsolete in the light of more recent technological developments. We cannot accept any responsibility for recommendations based solely on this document.

DUNLOP CONVEYOR BELTING (HEAD OFFICE) • Oliemolenstraat 2 • PO Box 14 • 9200 AA Drachten • The Netherlands •
 Tel.: +31 (0) 512 585 555 • Fax: +31 (0) 512 524 599
POLAND • Tel.: +48 (0) 32 218 5070 • **FRANCE** • Tel.: +33 (0) 13055 3903 • **SPAIN** • Tel.: +34 (0) 93 805 54 46 •
RUSSIA • Tel.: +7 495 7415410 • **ITALY** • Tel.: +39 (0) 363 906266 • **GERMANY** • Tel.: +49 (0) 1729 72 93 02 •
MOROCCO • Tel.: +212 (0) 522 34 65 80/85 •